

↳ eBee

senseFly



The **professional**
mapping drone

Technical specifications

Hardware

Weight (inc. supplied camera)	Approx. 0.69 kg (1.52 lbs)
Wingspan	96 cm (38 in)
Material	EPP foam, carbon structure & composite parts
Propulsion	Electric pusher propeller, 160 W brushless DC motor
Battery	11.1 V, 2150 mAh
Camera (supplied)	WX (18.2 MP)
Cameras (optional)	S110 RGB, thermoMAP
Carry case dimensions	55 x 45 x 25 cm (21.6 x 17.7 x 9.8 in)

Operation

Maximum flight time	50 minutes
Nominal cruise speed	40-90 km/h (11-25 m/s or 25-56 mph)
Radio link range	Up to 3 km (1.86 miles)
Maximum coverage (single flight)	12 km ² / 4.6 mi ² (at 974 m / 3,195 ft altitude AGL)
Wind resistance	Up to 45 km/h (12m/s or 28 mph)
Ground Sampling Distance (GSD)	Down to 1.5 cm (0.6 in) per pixel
Relative orthomosaic/3D model accuracy	1-3x GSD
Absolute horizontal/vertical accuracy (w/GCPs)	Down to 3 cm (1.2 in) / 5 cm (2 in)
Absolute horizontal/vertical accuracy (no GCPs)	1-5 m (3.3-16.4 ft)
Multi-drone operation	Yes (inc. mid-air collision avoidance)
Automatic 3D flight planning	Yes
Linear landing accuracy	Approx. 5 m (16.4 ft)

Package contents

- eBee foam body (inc. all electronics & built-in autopilot)
- Pair of detachable wings
- WX still camera (inc. 16 GB SD card, battery, USB cable & charger)
- 2.4 GHz USB radio modem for data link (inc. USB cable)
- Two Lithium-Polymer battery packs & charger
- Spare propeller
- Carry case with foam protection
- Remote control & accessories (for safety pilots)
- User manual
- eMotion flight planning & control software



For eBee updates
subscribe to our newsletter at
www.sensefly.com

